# NSN 5320-01-177-1685

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-177-1685

# Fastener Length:

0.475 inches

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

### Shank Diameter:

0.201 inches

### Head Major Diameter:

Between 0.349 inches and 0.357 inches

#### Expansion Device:

Serrated stem-type w

### Grip Length:

Between 0.251 inches and 0.312 inches

### Min. Tensile Strength (psi):

715 pounds per square inch

#### Shear Strength:

1165 single pounds per square inch

### **Countersink Angle:**

100.0 degrees

#### **Special Features:**

Oversize dia, for repair/replacement of nas1921b06-05

### Material:

Aluminum alloy

# Surface Treatment:

Anodize expander

### Test Data Document:

29666-osmls100 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### Shelf Life:

N/a

### Unit Of Measure:

```
--
```

### Demilitarization:

No

### Fiig:

A040a0