## NSN 5320-01-177-1688

Blind Rivet - Page 1 of 1

**Demilitarization:** 

No Fiig: A040a0



View Online at https://aerobasegroup.com/nsn/5320-01-177-1688 Fastener Length: 0.662 inches **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** 0.173 inches **Shank Style:** Self-plugging **Head Major Diameter:** Between 0.349 inches and 0.357 inches **Expansion Device:** Serrated stem-type w **Grip Length:** Between 0.438 inches and 0.500 inches Min. Tensile Strength (psi): 715 pounds per square inch **Shear Strength:** 1165 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Oversize dia, for repair/replacement of nas 1921b06-08 Material: Aluminum alloy **Surface Treatment:** Anodize expander **Test Data Document:** 29666-osmls100 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a **Unit Of Measure:**