## NSN 5320-01-177-3060

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-177-3060

Head	Sty	e:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:** 

Between 0.1970 inches and 0.1985 inches

**Shank Style:** 

Threaded self-plugging shank w/sleeve

**Head Major Diameter:** 

0.385 inches

**Expansion Device:** 

Threaded stem

Lubrication:

Dry film or cetyl alcohol or wax

**Grip Length:** 

Between 0.150 inches and 0.200 inches

**Countersink Angle:** 

Between 99.0 degrees and 101.0 degrees

Material:

Titanium alloy uns r56400 nut

## **Material Specification:**

Mil-t-9047 military specification single material response nut or ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut

**Surface Treatment:** 

Passivate sleeve

## **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response sleeve

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-t-9047 spec.