## NSN 5320-01-178-8419

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-178-8419 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.940 inches and 0.960 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style: Head Major Diameter:** 0.3536 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.630 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 258, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-178-8419

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0