NSN 5320-01-180-2572

Pin-rivet - Page 1 of 2

Thread Class:

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5320-01-180-2572

| Right-hand |
|--|
| Fastener Length: |
| Between 1.146 inches and 1.171 inches |
| Head Style: |
| Err-090 |
| Head Height: |
| Between 0.082 inches and 0.094 inches |
| Shank Diameter: |
| 0.3912 inches |
| Shank Style: |
| Pin-rivet, tapered, threaded |
| Head Major Diameter: |
| Between 0.567 inches and 0.581 inches |
| Tip Diameter: |
| 0.1376 inches |
| Lubrication: |
| Dry film and cetyl alcohol |
| Grip Length: |
| Between 0.740 inches and 0.755 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Thread Size: |
| 0.375 inches |
| Shear Strength: |
| 125000 single pounds per square inch |
| Material: |
| Steel comp xm-13 |
| Material Specification: |
| Ams 5629 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Q-p-35 federal specification 13th treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas1728 professional/industrial association standard |
| |

NSN 5320-01-180-2572

Pin-rivet - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0