## NSN 5320-01-180-4816

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-180-4816 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.260 inches and 1.280 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.5066 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.880 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 258, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-180-4816

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0