NSN 5320-01-180-7171

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-180-7171

| Fastener Length: |
|--|
| 1.446 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.186 inches and 0.190 inches |
| Shank Style: |
| Self-plugging mechanically locked stem |
| Head Major Diameter: |
| Between 0.349 inches and 0.357 inches |
| Expansion Device: |
| Serrated stem-type w |
| Grip Length: |
| Between 0.563 inches and 0.625 inches |
| Countersink Angle: |
| 100.0 degrees |
| Material: |
| Aluminum alloy 5056 sleeve |
| Material Specification: |
| Qq-a-430 federal specification all material responses |
| Surface Treatment: |
| Anodize stem or oxide film stem |
| Surface Treatment Specification: |
| Mil-a-8625 military specification 1st treatment response sleeve or mil-c-5541 military specification 2nd treatment response sleeve |
| Specification Data: |
| 80205-nas1921 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |
| Mil-a-8625 spec. |
| |