

View Online at <https://aerobasegroup.com/nsn/5320-01-180-9119>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.818 inches and 0.843 inches

Head Style:

Flush countersunk

Shank Diameter:

0.4365 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

0.630 inches

Tip Diameter:

0.3175 inches

Lubrication:

Dry film and cetyl alcohol

End Application:

Wsd: aircraft, eagle f-15

Grip Length:

Between 0.365 inches and 0.380 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Thread Size:

0.375 inches

Shear Strength:

125000 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0