NSN 5320-01-181-9323

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-181-9323

Factorial another
Fastener Length:
Between 0.428 inches and 0.448 inches
Head Style:
Universal
Head Height:
Between 0.067 inches and 0.077 inches
Shank Diameter:
Between 0.155 inches and 0.159 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
Between 0.296 inches and 0.328 inches
Heat Treatment:
Annealed
Material:
Titanium alloy uns r58450
Material Specification:
Ams 4982 assn standard single material response
Surface Treatment:
Aluminum
Aluminum Surface Treatment Specification:
Surface Treatment Specification:
Surface Treatment Specification: Nas4006 national specification single treatment response
Surface Treatment Specification: Nas4006 national specification single treatment response Shelf Life:
Surface Treatment Specification: Nas4006 national specification single treatment response Shelf Life: N/a
Surface Treatment Specification: Nas4006 national specification single treatment response Shelf Life: N/a Unit Of Measure:
Surface Treatment Specification: Nas4006 national specification single treatment response Shelf Life: N/a Unit Of Measure:
Surface Treatment Specification: Nas4006 national specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:
Surface Treatment Specification: Nas4006 national specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No
Surface Treatment Specification: Nas4006 national specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:
Surface Treatment Specification: Nas4006 national specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: