

View Online at <https://aerobasegroup.com/nsn/5320-01-182-1682>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.962 inches and 0.982 inches

Head Style:

Err-090

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1940 inches and 0.1945 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corporation and solid film

Grip Length:

0.567 inches

Thread Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Ti-shield iii, fscm 73197 mfr ref single treatment response or tiodize type 2, fscm 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0