NSN 5320-01-182-1683

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-182-1683 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.197 inches and 2.222 inches **Head Style:** Err-090 **Head Height:** Between 0.058 inches and 0.070 inches **Shank Diameter:** 0.2896 inches **Head Major Diameter:** Between 0.379 inches and 0.389 inches **Tip Diameter:** 0.2525 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.865 inches and 1.880 inches Min. Tensile Strength (psi): 180000 pounds per square inch Thread Size: 0.250 inches **Shear Strength:** 108000 single pounds per square inch Material: Steel comp 8740 or steel comp 4340 **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1728 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-182-1683

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.