NSN 5320-01-183-1515

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-183-1515 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.935 inches and 0.955 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.055 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2250 inches and 0.2255 inches **Shank Style: Head Major Diameter:** Between 0.295 inches and 0.315 inches Lubrication: Cetyl alcohol and cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.510 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield 3, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-183-1515

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0