# NSN 5320-01-184-3800

Pin-rivet - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5320-01-184-3800



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.627 inches and 1.647 inches

# Head Style:

Err-090

#### **Head Height:**

Between 0.045 inches and 0.055 inches

### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

1.317 inches

# Thready Qty Per Inch (tpi):

32

### **Thread Size:**

0.190 inches

## Shear Strength:

95000 single pounds per square inch

Material:

Titanium alloy uns r56400

### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

### **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

## Fiig:

A528u0