
# NSN 5320-01-184-7739

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.003 inches and 1.023 inches

### Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

## Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.295 inches and 0.315 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

0.693 inches

## Thready Qty Per Inch (tpi):

32

## Thread Size:

0.190 inches

## Shear Strength:

95000 single pounds per square inch

# Material:

Iron alloy 660

# Material Specification:

Ams 5737 assn standard single material response or ams 5731 assn standard single material response

# Surface Treatment:

Passivate

# Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 5320-01-184-7739

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

