NSN 5320-01-187-8789



Solid Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-187-8789 Fastener Length: Between 2.990 inches and 3.010 inches **Head Style:** Undersized oval countersunk **Head Height:** Between 0.004 inches and 0.006 inches **Shank Diameter:** Between 0.186 inches and 0.189 inches **Shank Style:** Straight w/radius chamfered tip **Head Major Diameter:** 0.3016 inches **Head Minor Diameter:** 0.198 mils and 0.208 centimeters **Countersink Height:** 0.046 inches **Shear Strength:** 41000 single pounds per square inch **Countersink Angle:** Between 99.5 degrees and 100.5 degrees **Heat Treatment:** T-73 solution heat treated Material: Aluminum alloy **Material Specification:** Qq-a-430 comp 7050 federal specification single material response **Surface Treatment:** Anodize or chromate **Surface Treatment Specification:** Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response **Specification Data:** 80205-nas1097 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.