NSN 5320-01-187-9576

Pin-rivet Collar - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-187-9576 **Thread Class: Thread Direction:** Right-hand **Identification Code Color:** Red **Collar Outside Diameter:** Between 0.610 inches and 0.620 inches Collarheight: 0.690 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Collar Inside Diameter:** 0.333 inches **Features Provided:** Washer Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.312 inches **Collar Style:** Threaded (break off) type **Special Features:** Washer material 17-7ph and 15-7mo heat treat to th1050 per mil-h-6875; washer has solid film lube **Heat Treatment:** T-6 solution heat treated collar Material: Steel comp 630 washer or steel comp 631 washer or steel comp 632 washer **Material Specification:** Qq-a-430 federal specification single material response collar or qq-a-225/6 federal specification single material response collar **Surface Treatment:** Anodize collar **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response body **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5320-01-187-9576

Pin-rivet Collar - Page 2 of 2



Fiig:

A530g0

Mil-std (military Standard):

Mil-a-8625 spec.