NSN 5320-01-188-1735

Pin-rivet Collar - Page 1 of 2

No



view Online at https://aerobasegroup.com/hsn/5320-01-166-1735
Thread Class:
3b
Thread Direction:
Right-hand
dentification Code Color:
Red
Collar Outside Diameter:
Between 0.355 inches and 0.365 inches
Collarheight:
0.445 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Collar Inside Diameter:
0.210 inches
Features Provided:
Washer
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Collar Style:
Threaded (break off) type
Special Features:
Washer material 17-7ph and 15-7mo heat treat to th1050 per mil-h-6875; washer has solid film lube
Heat Treatment:
Γ-6 solution heat treated collar
Material:
Steel comp 630 body or steel comp 631 body or steel comp 632 body
Material Specification:
Qq-a-430 federal specification single material response collar or qq-a-225/6 federal specification single material response collar
Surface Treatment:
Anodize collar
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response collar
Thread Series Designator:
Jnjf
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:

NSN 5320-01-188-1735

Pin-rivet Collar - Page 2 of 2



Fiig:

A530g0

Mil-std (military Standard):

Mil-a-8625 spec.