NSN 5320-01-189-5436

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-189-5436

view Offiline at https://defobasegroup.com/nsi//3320-01-103-3430
Fastener Length:
Between 0.493 inches and 0.503 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.003 inches and 0.007 inches
Shank Diameter:
Between 0.1890 inches and 0.1895 inches
Shank Style:
Straight with tapered tip
Head Major Diameter:
0.3016 inches
Head Minor Diameter:
Between 0.267 inches and 0.277 inches
Countersink Height:
0.046 inches
Chamfer Length:
Between 0.197 inches and 0.222 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 0.282 inches and 0.312 inches
Shear Strength:
95000 single pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
Tail material titanium-columbium alloy per ams 4982, heat treatment-annealed
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4967 assn standard single material response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A040a0