## NSN 5320-01-189-7546



Solid Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-189-7546 Fastener Length: Between 0.431 inches and 0.451 inches **Head Style:** Undersized oval countersunk **Head Height:** Between 0.003 inches and 0.007 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Straight with tapered tip **Head Major Diameter:** 0.3016 inches **Head Minor Diameter:** Between 0.267 inches and 0.277 inches **Countersink Height:** 0.046 inches **Chamfer Length:** Between 0.198 inches and 0.233 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.219 inches and 0.250 inches **Shear Strength:** 95000 single pounds per square inch 2, heat treatment-annealed

| Countersink Angle:                                  |
|---|
| Between 99.0 degrees and 101.0 degrees              |
| Special Features:                                   |
| Tail material titanium-columbium alloy per ams 4982 |
| Material:   |
| Titanium alloy uns r56400                           |
| Material Specification:                             |
| Ams 4967 assn standard single material response     |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:                                    |
|   |
| Demilitarization:                                   |
| No  |
| Fiig:   |
| A040a0  |
|   |