## NSN 5320-01-190-4108

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-190-4108 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.815 inches and 0.835 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.357 inches and 0.377 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.505 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.190 inches **Special Features:** Furnished with one collar Material: Steel comp h11 **Material Specification:** Ams6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams2416 assn standard single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

## NSN 5320-01-190-4108

Pin-rivet - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A528u0