## NSN 5320-01-190-7629

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-190-7629 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.440 inches and 0.460 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2021 inches and 0.2026 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.3146 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** 0.130 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

Qq-p-35 federal specification single treatment responsible.

Unjf

Shelf Life:
N/a

Unit Of Measure:
--

## NSN 5320-01-190-7629

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0