# NSN 5320-01-191-2540

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-191-2540

## Fastener Length:

Between 0.368 inches and 0.388 inches

## Head Style:

Undersized oval countersunk

# Head Height:

Between 0.003 inches and 0.007 inches

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Straight with tapered tip

## Head Major Diameter:

0.3016 inches

## Head Minor Diameter:

Between 0.267 inches and 0.277 inches

## **Countersink Height:**

0.046 inches

## Chamfer Length:

Between 0.197 inches and 0.232 inches

Lubrication:

Cetyl alcohol

# Grip Length:

Between 0.157 inches and 0.187 inches

# Shear Strength:

95000 single pounds per square inch

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

## **Special Features:**

Tail material titanium-columbium alloy per ams 4982, heat treatment-annealed

## Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams 4967 assn standard single material response

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A040a0