

View Online at <https://aerobasegroup.com/nsn/5320-01-192-6711>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.510 inches and 1.530 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2490 inches and 0.2495 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

0.5066 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

Wsd: aircraft, b-1b

**Grip Length:**

1.130 inches

**Thread Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.250 inches

**Countersink Angle:**

100.0 degrees

**Criticality Code Justification:**

Feat

**Special Features:**

Weapon system essential

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0