# NSN 5320-01-193-0244

Pin-rivet - Page 1 of 2





# Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.363 inches and 1.383 inches

## Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

## Shank Diameter:

Between 0.2802 inches and 0.2807 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.4260 inches

#### Lubrication:

Dry film and cetyl alcohol

## Grip Length:

0.943 inches

# Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

## Shear Strength:

125000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### Material:

Steel comp xm-13

## **Material Specification:**

Ams 5629 assn standard single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-193-0244

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

