## NSN 5320-01-193-4550

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-193-4550 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.864 inches and 0.884 inches **Head Style:** Err-090 **Head Height:** Between 0.037 inches and 0.047 inches Width Between Flats: Between 0.0635 inches and 0.0645 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.242 inches and 0.262 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.567 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 258 fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5320-01-193-4550

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0