# NSN 5320-01-193-6955

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-193-6955



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.760 inches and 0.780 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.059 inches and 0.069 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2641 inches and 0.2651 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.387 inches and 0.412 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## End Application:

W/s: joint stars target radar system; aircraft, stratolifter c-135

#### Grip Length:

0.380 inches

## Thready Qty Per Inch (tpi):

28

#### Thread Size:

0.250 inches

#### **Special Features:**

Color code green on threads

#### Material:

Iron alloy 660

#### Material Specification:

Ams 5737 assn standard single material response or ams 5731 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-193-6955

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

