NSN 5320-01-194-0432



Solid Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-194-0432 Fastener Length: Between 0.851 inches and 0.871 inches **Head Style:** Undersized oval countersunk **Head Height:** Between 0.003 inches and 0.007 inches **Shank Diameter:** Between 0.1635 inches and 0.1640 inches **Shank Style:** Straight with tapered tip **Head Major Diameter:** 0.2469 inches **Head Minor Diameter:** Between 0.215 inches and 0.225 inches **Countersink Height:** 0.034 inches **Chamfer Length:** Between 0.180 inches and 0.215 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.657 inches and 0.687 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Tail material titanium-columbium alloy per ams 4982, heat treatment annealed

| Material: |
|---|
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams 4967 assn standard single material response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |