

View Online at <https://aerobasegroup.com/nsn/5320-01-194-3046>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.052 inches and 1.072 inches

Head Style:

Err-090

Head Height:

Between 0.098 inches and 0.112 inches

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3271 inches and 0.3276 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.472 inches and 0.502 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.567 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.312 inches

Shear Strength:

95000 single pounds per square inch

Material:

Iron alloy 660

Material Specification:

Ams 5737 assn standard single material response or ams 5731 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0