NSN 5320-01-194-3050

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-194-3050 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.760 inches and 0.780 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.5066 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.380 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees **Special Features:** Furnished with one collar Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams2416 assn standard single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5320-01-194-3050

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0