NSN 5320-01-194-7084

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-194-7084

Thread Class:
3b
Thread Direction:
Right-hand
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.309 inches and 0.312 inches
Shank Style:
Blind rivet, nut and bolt (assembly)
Head Major Diameter:
0.372 inches
Expansion Device:
Expander
Lubrication:
Solid film
Grip Length:
Between 0.4325 inches and 0.4525 inches
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Shear Strength:
110000 single pounds per square inch
Countersink Angle:
Between 98.0 degrees and 102.0 degrees
Special Features:
Without bolt. Shear strength and lubrication apply to expander only
Heat Treatment:
Annealed sleeve
Material:
Steel comp 305 sleeve
Material Specification:
Qq-s-763 federal specification single material response sleeve
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5320-01-194-7084

Blind Rivet - Page 2 of 2



Fiig:

A040a0