NSN 5320-01-195-2992

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-195-2992

Fastener Length:
1.218 inches
Head Style:
Straight pan
Head Height:
Between 0.131 inches and 0.141 inches
Shank Diameter:
Between 0.310 inches and 0.312 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
Between 0.480 inches and 0.522 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 0.781 inches and 0.845 inches
Min. Tensile Strength (psi):
5200 pounds per square inch
Hardness Rating:
48.0 rockwell c stem and 53.0 rockwell c stem
Shear Strength:
8500 single pounds per square inch
Material:
Steel comp 8740 stem
Material Specification:
Qq-w-405 federal specification 1st material response sleeve or mil-s-6758 military specification 2nd material response sleeve
Surface Treatment:
Cadmium stem
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve
Specification Data:
96906-ms90354 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil = 0040 array

Mil-s-6049 spec.