

View Online at <https://aerobasegroup.com/nsn/5320-01-195-3019>

**Fastener Length:**

1.000 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.130 inches and 0.140 inches

**Shank Diameter:**

Between 0.258 inches and 0.260 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.400 inches and 0.432 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.844 inches and 0.907 inches

**Min. Tensile Strength (psi):**

3650 pounds per square inch

**Hardness Rating:**

48.0 rockwell c stem and 53.0 rockwell c stem

**Shear Strength:**

5900 single pounds per square inch

**Material:**

Steel comp 8740 stem

**Material Specification:**

Qq-w-405 federal specification 1st material response sleeve or mil-s-6758 military specification 2nd material response sleeve

**Surface Treatment:**

Cadmium stem

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve

**Specification Data:**

96906-ms90354 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6049 spec.