## NSN 5320-01-197-2467

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-197-2467 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 1.425 inches and 1.445 inches **Head Style:** Err-090 **Head Height:** Between 0.103 inches and 0.115 inches Width Between Flats: Between 0.2207 inches and 0.2242 inches **Shank Diameter:** Between 0.4985 inches and 0.4995 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.735 inches and 0.770 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.755 inches Thready Qty Per Inch (tpi): 20 **Hardness Rating:** 45.0 rockwell c and 48.0 rockwell c **Thread Size:** 0.500 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:**No

## NSN 5320-01-197-2467

Pin-rivet - Page 2 of 2



Fiig:

A528u0