
# NSN 5320-01-197-2467

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.425 inches and 1.445 inches

# Head Style:

Err-090

#### Head Height:

Between 0.103 inches and 0.115 inches

#### Width Between Flats:

Between 0.2207 inches and 0.2242 inches

#### Shank Diameter:

Between 0.4985 inches and 0.4995 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.735 inches and 0.770 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

0.755 inches

# Thready Qty Per Inch (tpi):

20

## Hardness Rating:

45.0 rockwell c and 48.0 rockwell c

## **Thread Size:**

0.500 inches

# Shear Strength:

125000 single pounds per square inch

#### Material:

Steel comp h11

## Material Specification:

Ams 6487 assn standard single material response

## **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-197-2467

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

