## NSN 5320-01-199-1382

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-199-1382 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.823 inches and 0.843 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches Lubrication: Solid film **Grip Length:** 0.443 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Heat Treatment:** T-6 solution heat treated Material: Aluminum alloy 7075 **Material Specification:** Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-199-1382

Pin-rivet - Page 2 of 2



| em |  |  |  |
|----|--|--|--|
|    |  |  |  |
|    |  |  |  |

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.