## NSN 5320-01-200-4018

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-200-4018 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.910 inches and 0.950 inches **Head Style:** Err-090 **Head Height:** Between 0.042 inches and 0.050 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2016 inches and 0.2026 inches **Shank Style: Head Major Diameter:** Between 0.298 inches and 0.312 inches **Grip Length:** Between 0.563 inches and 0.625 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches Material: Steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas4450 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5320-01-200-4018

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.