

View Online at <https://aerobasegroup.com/nsn/5320-01-200-4018>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.910 inches and 0.950 inches

Head Style:

Err-090

Head Height:

Between 0.042 inches and 0.050 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.2016 inches and 0.2026 inches

Shank Style:

Head Major Diameter:

Between 0.298 inches and 0.312 inches

Grip Length:

Between 0.563 inches and 0.625 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas4450 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.