## NSN 5320-01-201-8811

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-201-8811 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.487 inches and 2.507 inches **Head Style:** Err-090 **Head Height:** Between 0.178 inches and 0.188 inches Width Between Flats: Between 0.2207 inches and 0.2242 inches **Shank Diameter:** Between 0.5297 inches and 0.5307 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.740 inches and 0.775 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.817 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.500 inches **Shear Strength:** 95000 single pounds per square inch Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-201-8811

Pin-rivet - Page 2 of 2



Der	nilit	ariz	atio	n:

No

Fiig:

A528u0