NSN 5320-01-203-0925



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-203-0925 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.035 inches and 1.055 inches **Head Style:** Err-090 **Head Height:** Between 0.130 inches and 0.140 inches Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.530 inches and 0.565 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.505 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 95000 single pounds per square inch Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5320-01-203-0925

Pin-rivet - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A528u0