

View Online at <https://aerobasegroup.com/nsn/5320-01-204-4780>

**Fastener Length:**

0.342 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.162 inches and 0.164 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

0.333 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.156 inches and 0.220 inches

**Hardness Rating:**

48.0 rockwell c stem and 53.0 rockwell c stem

**Shear Strength:**

112000 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel

**Material Specification:**

Astm a331 assn standard single material response

**Surface Treatment:**

Cadmium stem or aluminum stem

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification 1st treatment response sleeve or mil-c-83488 military specification 2nd treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-c-83488 spec.