

View Online at <https://aerobasegroup.com/nsn/5320-01-204-9456>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.003 inches and 1.023 inches

Head Style:

Err-090

Width Between Flats:

Between 0.079 inches and 0.080 inches

Shank Diameter:

Between 0.1630 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.2564 inches and 0.2612 inches

Lubrication:

Solid film

Grip Length:

Between 0.683 inches and 0.693 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Shear Strength:

5380 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Hi kote 2 solid film lube per hi-shear spec. 292 and cetyl alcohol lube per hi-shear specification 305

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Ti-shield iii mfr ref all treatment responses

Thread Series Designator:

Unjf

Specification Data:

73197-hlt311ta-5-11 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0