NSN 5320-01-206-0128

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-206-0128



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.565 inches and 0.585 inches

Head Style:

Err-090

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Grip Length:

Between 0.240 inches and 0.260 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

Hole 0.081 in. Dia; 0.166 in. From threaded endto center of hole

Material:

Iron alloy 660

Material Specification:

Ams 5732 assn standard 1st material response or ams 5731 assn standard 2nd material response

Surface Treatment:

Passivate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-206-0128

Pin-rivet - Page 2 of 2

Fiig: A528u0

