## NSN 5320-01-206-1767

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-206-1767



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 1.678 inches and 1.698 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.068 inches and 0.078 inches

#### Width Between Flats:

Between 0.127 inches and 0.130 inches

#### Shank Diameter:

Between 0.342 inches and 0.343 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.475 inches and 0.505 inches

#### End Application:

Aircraft model a-10

#### Grip Length:

Between 1.183 inches and 1.193 inches

#### Thready Qty Per Inch (tpi):

24

#### **Thread Size:**

0.344 inches

#### Material:

Steel comp 4140 or steel comp 8740

#### Material Specification:

Mil-s-5656 military specification 1st material response or mil-s-6049 military specification 2nd material response

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Qq-p-416, type 11, class 2 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-01-206-1767

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-s-5656 spec.

