NSN 5320-01-206-3502



Pin-rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-206-3502 Fastener Length: Between 1.098 inches and 1.118 inches **Head Style:** Err-090 **Head Height:** Between 0.099 inches and 0.111 inches **Shank Diameter:** Between 0.2010 inches and 0.2025 inches **Shank Style:** Pin-rivet, multiple grooved **Head Major Diameter:** Between 0.297 inches and 0.327 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.845 inches and 0.906 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 77.0 rockwell superficial 15-n and 82.0 rockwell superficial 15-n **Shear Strength:** 95000 single pounds per square inch Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Material Specification:** Astm a547 assn standard single material response **Surface Treatment:** Cadmium and chromate nse

Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Specification Data:
80205-nas1466 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A528u0