NSN 5320-01-206-7398

Pin-rivet - Page 1 of 1

A528u0



View Online at https://aerobasegroup.com/nsn/5320-01-206-7398 **Head Style:** Err-090 **Head Height:** Between 0.099 inches and 0.111 inches Shank Diameter: Between 0.2010 inches and 0.2025 inches **Shank Style:** Pin-rivet, multiple grooved **Head Major Diameter:** Between 0.297 inches and 0.327 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.345 inches and 1.406 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 77.0 rockwell superficial 15-n and 82.0 rockwell superficial 15-n **Shear Strength:** 95000 single pounds per square inch Material: Steel comp 8740 or steel comp 4340 or steel comp 4140 **Material Specification:** Aisi assn standard 1st material response or aisi assn standard 2nd material response or astm a547 assn standard 3rd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Specification Data:** 80205-nas1466 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: