## NSN 5320-01-207-5144

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-207-5144 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.690 inches and 0.710 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches **Hole Diameter:** Between 0.104 inches and 0.119 inches **Shank Diameter:** Between 0.1810 inches and 0.1840 inches **Shank Style:** Err-090 **Head Major Diameter:** Between 0.357 inches and 0.377 inches **Hole Depth:** Between 0.115 inches and 0.135 inches **Grip Length:** Between 0.370 inches and 0.380 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches Material: Titanium alloy **Material Specification:** Ams4928, 6al-4v assn standard single material response or ams4967, 6al-4v assn standard single material response **Surface Treatment:** Cadmium **Thread Series Designator:** Unjf **Specification Data:** 73197-hl512 manufacturers standard Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-207-5144

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0