

View Online at <https://aerobasegroup.com/nsn/5320-01-207-7674>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.473 inches and 1.493 inches

Head Style:

Err-090

Head Height:

Between 0.130 inches and 0.140 inches

Width Between Flats:

Between 0.1582 inches and 0.1617 inches

Shank Diameter:

Between 0.4047 inches and 0.4057 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.550 inches and 0.620 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.943 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.375 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

Color code green on threads

Material:

Iron alloy 660

Material Specification:

Ams 5737 assn standard single material response or ams 5731 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0