## NSN 5320-01-208-3881

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-208-3881

Fastener Length:  1.580 inches  Head Style:  Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)  Shank Diameter:  Between 0.124 inches and 0.128 inches  Shank Style:  Self-plugging mechanically locked stem	
Head Style: Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) Shank Diameter: Between 0.124 inches and 0.128 inches Shank Style:	
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)  Shank Diameter:  Between 0.124 inches and 0.128 inches  Shank Style:	
Shank Diameter: Between 0.124 inches and 0.128 inches Shank Style:	
Between 0.124 inches and 0.128 inches  Shank Style:	
Shank Style:	
Self-plugging mechanically locked stem	
Head Major Diameter:	
0.229 inches	
Expansion Device:	
Serrated stem-type w	
Grip Length:	
Between 0.626 inches and 0.687 inches	
Countersink Angle:	
Between 99.0 degrees and 101.0 degrees	
Material:	
Iron alloy 660 stem	
Material Specification:	
Ams 5732 assn standard single material response or ams 5731 assn standard single material response or	ams 5737 assn standard single
material response stem	
Surface Treatment:	
Passivate	
Surface Treatment Specification:	
Qq-p-35 federal specification single treatment response	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A040a0	