## NSN 5320-01-209-7377

Pin-rivet - Page 1 of 2

**Thread Class:** 

**Thread Direction:** 

3a

View Online at https://aerobasegroup.com/nsn/5320-01-209-7377



## **Right-hand** Identification Code Color: Natural **Fastener Length:** Between 1.010 inches and 1.030 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches Shank Diameter: Between 0.2485 inches and 0.2495 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.387 inches and 0.412 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: 0.630 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Heat Treatment:** T-6 solution heat treated Material: Aluminum alloy 7075 **Material Specification:** Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response Surface Treatment: Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## NSN 5320-01-209-7377

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.

