## NSN 5320-01-209-9473

Solid Rivet - Page 1 of 2

A040a0



View Online at https://aerobasegroup.com/nsn/5320-01-209-9473

Fastener Length:
Between 0.865 inches and 0.885 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.004 inches and 0.006 inches
Shank Diameter:
Between 0.186 inches and 0.189 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
0.3016 inches
Head Minor Diameter:
Between 0.198 inches and 0.208 inches
Countersink Height:
0.046 inches
Shear Strength:
24000 single pounds per square inch
Countersink Angle:
Between 99.5 degrees and 100.5 degrees
Special Features:
Optional squared end
Heat Treatment:
T-73 solution heat treated
Material:
Aluminum alloy 7050
Material Specification:
Qq-a-430, temper t73 federal specification single material response
Surface Treatment:
Anodize or chromate
Surface Treatment Specification:
Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response
Specification Data:
80205-nas1097 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

## NSN 5320-01-209-9473

Solid Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.